

### Interlam™ EcoGloss



#### Product Description

Interlam™ EcoGloss is a 40µ (1.6 mil) gloss finish polypropylene laminating film coated on one side with a pressure sensitive, aqueous acrylic adhesive, which is protected by a bleached Kraft release paper coated on one side with siliconised polyethylene. Interlam™ EcoGloss has a recyclability code of 5PP. Available in various sizes.

#### Applications

Interlam™ EcoGloss is particularly suitable for POP displays, indoor and short term outdoor signage, architectural renderings, maps and other indoor promotional graphics to be used under direct light. This product is not recommended for laminating vinyl banners or other applications where the laminate will be required to expand and contract with the print media.

#### Product Structure

Film:	Gloss finish polypropylene	↕ 65µ (2.6 mil)
Adhesive:	Aqueous Acrylic (pressure sensitive)	
Release Liner:	1 Side PE coated siliconised Kraft Paper	

#### General Properties

Film Thickness	40µ (1.6 mil)
Adhesive Layer	25µ (1 mil)
Ratio Film to Adhesive	1.6:1
UV Protection Factor	Adhesive contains UV stabilisers, which prevent film degradation and provides UV protection to the underlying image.
Outdoor Durability	Up to 2 years
Heat Resistance Range	110°C to 120°C (230°F to 248°F)
Peel Strength (20 min, FTM1)	11 N/25mm

#### Process Settings

Roller Laminator	Vacuum Press
Temp: Room temp to 49°C (120°F) Speed: 0.3m to 2.5m (1ft to 8ft) per minute	NOT RECOMMENDED

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to careful quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale.

Drytac Europe Ltd (UK) - Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660  
Drytac Corp. (USA) - 5601 Eastport Boulevard, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610  
Drytac Canada Inc. (Canada) - 137 Buttermill Avenue, Concord, Ontario, L4K 3X5, Canada. Tel: 1-800-353-288