



2580+

Lexmark Forms Printer 2580+ Series

Fast, Reliable Forms Printing

The Lexmark Forms Printer 2580+ series provides high-speed forms printing and features such as high-yield ribbons, multi-part form support, and character and page monitoring.

Reliability and performance

With fast print speeds up to 618 cps at 12 cpi and a rugged design that can handle extreme environments and workloads, the Lexmark Forms Printer 2580+ series helps you to be productive no matter where you are. Benefit from the 2MB of built-in flash memory that expands support for bar codes, non-volatile fonts and remote management.

Flexible paper handling

Easily switch between push and pull feeds and select the type of paperhandling that best suits your needs. Use the optional Automatic Sheet Feeder to load stacks of cut-sheet media, envelopes or multi-part forms. Use the Tractor 2 option to simultaneously load two types of continuous forms.

Flexible media support

Print on multiple types of media, including single-part or multi-part continuous forms, and single-part or multi-part cut forms. Multi-part forms can include one original and up to five copies.

Easy to use

The easy-to-use operator panel lets you access all of the printer functions, as well as monitor printer usage with character and page counts. The panel also includes a font preview, so you can make sure that the correct font is used on your document.



Easy to maintain

For multi-national groups, the universal power supply reduces the need to maintain separate low-voltage and high-voltage power supplies. On the 2580n+ and 2581n+, the embedded web server and Lexmark Markvision Enterprise help you easily maintain multiple devices from a centralized location.

Easy to connect

Connecting to your network is easy and secure with built-in Ethernet and security features such as IPSec, HTTPS, SNMPv3 and 802.1x authentication with the Forms Printer 2580n+ and 2581n+.

Long lasting supplies

Replace supplies less often with powerful printheads that last up to 300 million characters and the availability of re-inking ribbons that can print up to 8 million characters.

2580+ Series Printer Features



Mono



Up to 618 cps at 12 cpi



Multi-Part Forms



Network Model

Product Specifications	Lexmark Forms Printer 2580+	Lexmark Forms Printer 2580n+	Lexmark Forms Printer 2581+	Lexmark Forms Printer 2581n+
Printing				
Printer Part Number	11C0099	11C0109	11C0111	11C2956
Print Technology	9-Pin Dot Matrix			
Print Speeds	Up to 618 cps Fast Draft @ 12 cpi, Up to 400 cps Draft @ 12 cpi, Up to 100 cps Near Letter Quality @ 12 cpi			
Maximum Print Line	8.0 inches		13.6 inches	
Resolution	240 x 144 dots per inch			
Memory	512 KB			
Mean Time Between Failures (MTBF)	12,500 POH @ 25% duty cycle			
Supplies Yield	Optional 8 million characters (draft mode at 10 cpi)- Re-Inking Ribbon, Standard 4 million characters (draft mode at 10 cpi) - Re-Inking Ribbon			
Supplies Part Number	3070169 - High Yield Black Re-Inking Ribbon 3070166 - Standard Yield Black Re-inking Ribbon			
Text Fonts	Fast Draft, Draft, Courier, Gothic, 10, 12, 15, 17.1, 20 cpi, Proportional Spaced (PS)			
Noise Level, Idle	0 dBA			
Print Noise Level, Operating	56 dBA			
Paper Handling				
Paper Handling Standard	Front Tractor Feeder			
Paper Handling Optional	Automatic Sheet Feeder (narrow), Tractor 2 (narrow)		Automatic Sheet Feeder (wide), Tractor 2 (wide)	
Paper Option Part Number	12T0693 - 2480, 2490 Automatic Sheet Feed (narrow) 12T0695 - 2480, 2490 Tractor 2 12T0697 - 2400 Cut Sheet Output Support Stand		12T0696 - 2481, 2491 Tractor 2 12T0694 - 2481, 2491, 4227+ Automatic Sheet Feed (wide) 12T0697 - 2400 Cut Sheet Output Support Stand	
Media Sizes Supported	Single-part or multi-part Continuous Forms, Narrow Sheet Fed Paper, Single-part or multi-part Cut Forms		Single-part or multi-part Continuous Forms, Wide Sheet Fed Paper, Single-part or multi-part Cut Forms	
Media Types Supported	Multi-part forms - Up to 1+5 Parts (up to 0.020" or 0.51 mm paper thickness), Single-part forms - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11 mm paper thickness), Forms or Paper - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11 mm maximum paper thickness)			
General				
Size (in. - H x W x D)	7.7 x 19.4 x 11.4 in.		7.7 x 24.9 x 11.4 in.	
Weight (lb.)	17.6 lb.		21.6 lb.	
Product Warranty	2-Year Exchange Service, Next Business Day			
Product Certifications	www.lexmark.com			
Specified Operating Environment	Humidity: 8 to 90% Relative Humidity, Temperature: 10 to 40°C (50 to 104°F)			
Compatibility				
Linux Operating Systems Supported	Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, Debian GNU/Linux 3.1, 4.0, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2			
Microsoft Windows Operating Systems Supported	2000, XP, Server 2003, XP x64, Server 2003 x64, Vista, Vista x64, Server 2008, Server 2008 x64, Windows 7, Windows 7, Server 2008 R2			
Standard Ports	Centronics IEEE 1284 Bidirectional Parallel, USB	Ethernet 10/100BaseTX (RJ-45), USB	Centronics IEEE 1284 Bidirectional Parallel, USB	Ethernet 10/100BaseTX (RJ-45), USB
Optional Local Ports	Internal RS-232C serial		Internal RS-232C serial	
Optional Network Ports	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB), External MarkNet™ N7002e Fast Ethernet (parallel)	External MarkNet™ N7020e Gigabit Ethernet	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB), External MarkNet™ N7002e Fast Ethernet (parallel)	External MarkNet™ N7020e Gigabit Ethernet
Printer Languages (Standard)	Epson Emulation, Personal Printer Data Stream (PPDS), Okidata MICROLINE Emulation			

Which model is best for you?



2580+	2580n+	2581+	2581n+
9-pin	9-pin	9-pin	9 pin
Narrow format	Narrow format	Wide format	Wide format
	Network ready		Network ready



www.lexmark.com

Lexmark, Lexmark with diamond design, and MarkNet are trademarks of Lexmark International, Inc. or its subsidiaries, registered in the United States and/or other countries. All other trademarks are the property of their respective owners. © 2014 Lexmark International, Inc. 740 W. New Circle Rd. Lexington, KY 40550. Information in this document is subject to change without notice.